

PARKLIO™ CHAIN

TECHNICAL SPECIFICATIONS



Automatic with remote control on your smartphone

24VDC chain barrier for residential and collective use

Up to 20m width passage barrier

High usage factor

Obstacle detection

Self-learning of open/close distances (encoder)

Electronic soft start-soft stop

Use of external limit switches (encoder)

Housing for battery backup

Downloadable application for your smartphone

A temporary digital key for your visitors

Power supply (Vac/Hz)	230/50
Power consumed (W)	170
Absorbed current (A)	5,5
Motor voltage (Vdc)	24
Opening time (s)	10
Lock	Yes
Limit switches	No
Encoder	Yes
Duty cycle	Intensive use
Protection level	IP54
Operating temperature (°C)	-20/60
Motor weight (kg)	46
Packaging dimensions (cm)	25 X 22 X 108
Chain maximum length (m)	20
Length of the chain (m)	4, 6, 8, 10, 12, 14, 16, 18, 20
Relative height in the middle (cm)	75, 70, 65, 60, 55, 50, 45, 40, 35

INSTRUCTIONS AND SUPPORT:

www.parklio.com/support/

APPLICATION DOWNLOAD:

(Android)

https://play.google.com/store/apps/details?id=com.parklio.parklio746237&hl=en_US

(Apple)

<https://itunes.apple.com/hr/app/parklio/id1316429271?mt=8>